



轴径 Shaft Diameter	轴承型号 Bearing Designation	重量 Mass 近似 Approx	外形尺寸 Boundary Dimensions			基本额定负荷 Basic Load Rating		极限转速 Limiting Speed
	现行的 Current		Fw	D	C	动 Cr Dynamic	静 Cor Static	油润滑 Oil
mm		g	mm			N		rpm
8	HK0810RS	2.9	8	12	10	2250	2100	19000
	HK08122RS	3.5	8	12	12	2250	2100	19000
9	HK09×13×12RS	4	9	13	12	3800	4300	19000
10	HK1012RS	4.2	10	14	12	4100	5000	19000
	HK10142RS	5.2	10	14	14	4100	5000	15000
12	HK1214RS	10.7	12	18	14	6100	7000	15000
	HK12162RS	11.5	12	18	16	6100	7000	12000
13	HK13×19×12RS	8.9	13	19	12	6800	7580	12000
14	HK1414RS	12	14	20	14	6100	7500	13000
	HK14162RS	14	14	20	16	6100	7500	11000
	BK1414RS	14.1	14	20	14	6100	7500	11000
15	HK1514RS	12.6	15	21	14	6800	8800	11000
	HK15162RS	14.3	15	21	16	6800	8800	10000
	BK1514RS	14.4	15	21	14	6800	8800	10000
	HK15202RS	18	15	21	20	9500	11400	10000
16	HK1614RS	15.1	16	22	14	7200	9200	10000
	HK16162RS	15.1	16	22	16	7200	9200	10000
	BK1614RS	15.3	16	22	14	7200	9200	10000
	HK16252RS	17.2	16	22	25	9900	12300	10000
17	HK17×25×14RS	17.7	17	25	14	8000	9800	10000
	HK17×25×20RS	26.2	17	25	20	11600	13200	13000
18	HK1814RS	15.1	18	24	14	7800	9900	13000
	HK18162RS	17	18	24	16	7800	9900	9200
20	HK2012RS	11.7	20	26	12	9500	11900	9200
	HK20162RS	18.8	20	26	16	8000	10100	9000
	HK20202RS	23.5	20	26	20	12700	20100	7800
	BK2018RS	24.4	20	26	18	12700	20100	7800
	HK20×29×18RS	28.8	20	29	18	8700	9980	7800
22	HK2212RS	14	22	28	12	8310	10000	9000
	HK22162RS	20.3	22	28	16	9000	12400	7800
	HK22202RS	25.5	22	28	20	10400	20100	7800
25	HK25162RS	27.3	25	32	16	9800	13200	6900
	HK2518RS	31	25	32	18	13600	20000	6900
	HK25202RS	33.1	25	32	20	13600	20000	6900
	BK2518RS	35.3	25	32	18	13600	20000	6900
28	HK25302RS	47.3	25	32	30	24500	43000	6900
	HK28202RS	36.9	28	35	20	11400	22500	5300
30	HK30162RS	28.5	30	37	16	10100	16200	5300
	HK3018RS	36.6	30	37	18	16200	26000	5300
	HK30242RS	49.7	30	37	24	21000	38500	5300
35	HK35162RS	36.4	35	42	16	10100	20300	4900
	HK3518RS	37.4	35	42	18	16700	30500	4900
	HK35202RS	41.1	35	42	20	16700	30500	4900
40	HK40162RS	41.2	40	47	16	11000	21300	4200
	HK4018RS	47.3	40	47	18	19000	30500	4200
	HK40202RS	50.2	40	47	20	19000	30500	4200
45	HK4518RS	52.2	45	52	18	20300	41000	3800
	HK45202RS	57.4	45	52	20	20300	41000	3800
50	HK5022RS	77.2	50	58	22	30000	61000	3200
	HK50242RS	84	50	58	24	30000	61000	3200

密封圈材质为尼龙66或聚四氟乙烯，其工作温度范围分别为-30℃~+100℃或-30℃~+180℃，宽度偏差-0.25mm，特殊要求订货时说明。